

## Safety Data Sheet acc. to OSHA HCS

Printing date 09/12/2014 Version 6 Reviewed on 09/12/2014

#### 1 Identification

· Product identifier

Einpressfluid OH 723 · Product name:

A100437 · Product code: · Former product code (till July 2012): 43100

Application of the substance / the

mixture

Industrial use

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

oelheld GmbH Ulmer Str. 135-139 70188 Stuttgart **GERMANY** 

Tel.: +49-(0)711-16863-0 Fax.: +49-(0)711-16863-40 E-Mail: hutec@oelheld.de Internet: www.oelheld.de

Department of research and development · Information department:

+49-(0)711-16863-72 msds@oelheld.de

· Emergency telephone number: during hours of business see above

out of office hours in German (or English): Dr. Schnödt Tel. +49 71 11 68 63-997 Mr. Philipp Storr Tel. +49 71 11 68 63-992 Mr. Martin Storr Tel. +49 71 11 68 63-993 Mr. Speth Tel. +49 71 11 68 63-994 see above or contact a Poison Control Center

### 2 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of synthetic aliphatic hydrocarbons

Dangerous components:

68649-11-6 1-Decene, Dimer, Hydrogenated

Xn R20-65 🗞 Asp. Tox. 1, H304; 🕧 Acute Tox. 4, H332

Additional information: For the wording of the listed risk phrases refer to section 16.

The GHS-classifications which are shown here for the dangerous components are classified according the rules of the European GHS (Regulation (EC) No 1272/2008).

STIHL Press Fluid

STIHL Incorporated

Distributed by:

536 Viking Drive

757-486-9100

STIHL Part No. 0781-957-9000

Virginia Beach, Virginia 23452

## 3 Hazard(s) identification

Classification of the substance or mixture

· Information concerning particular

hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General

Classification guideline for preparations of the EU" in the latest valid version.

· Classification system: The classification was made according to the latest editions of international substances

lists, and expanded upon from company and literature data.

· Label elements

Labelling according to EU

quidelines:

The product has been classified and marked in accordance with directives on hazardous

Observe the general safety regulations when handling chemicals.

· Code letter and hazard designation

of product:

· Risk phrases:

Harmful

Hazard-determining components of

1-Decene, Dimer, Hydrogenated

labeling:

20 Harmful by inhalation.

65 Harmful: may cause lung damage if swallowed.

23 Do not breathe vapour/spray. · Safety phrases:

51 Use only in well-ventilated areas.

62 If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label

· Hazard description:

· WHMIS classification D1B - Toxic material causing immediate and serious toxic effects WHMIS: workplace hazardous materials information system (Canadian)



(Contd. of page 1)



# Safety Data Sheet acc. to OSHA HCS

Printing date 09/12/2014 Version 6 Reviewed on 09/12/2014

Product name: Einpressfluid OH 723

· Classification system:

NFPA ratings (scale 0 - 4)

Health = 1Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)

Health = 1 1 Fire = 1REACTIVITY Reactivity = 0

· Other hazards

The NFPA- and the HMIS-ratings range from 0 (least severe hazard) to 4 (most severe

hazard).

NFPA and HMIS are regulations in the USA. NFPA: National Fire Protection Association HMIS: Hazardous Material Identification System

4 First-aid measures

· General information: Remove any clothing soiled by the product.

In case of occuring of symptoms or in doubt consult a doctor. If a doctor is consulted show this material safety data sheet.

· After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor

if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Wash with water and soap and rinse thoroughly.

After eve contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a

doctor.

· After ingestion: Do not induce vomiting; immediately call for medical help.

5 Fire-fighting measures

· Suitable extinguishing media: CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

Water with full jet

· For safety reasons unsuitable extinguishing media:

Special hazards arising from the

substance or mixture

In certain fire conditions, traces of other toxic gases cannot be excluded, e.g.: Carbon monoxide (CO) Wear self-contained respiratory protective device.

· Protective equipment: Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official

regulations.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency

procedures

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product. · Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

Keep contaminated washing water and dispose of appropriately.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders,

Dispose contaminated material as waste according to item 13.

· Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling Ensure good ventilation/exhaust at the workplace.

Open and handle receptacle with care. Prevent formation of aerosols.

· Information about protection against

explosions and fires:

Fumes can combine with air to form an explosive mixture above the flash point.

Storage:

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Information about storage in one

common storage facility:

Not required.

(Contd. on page 3)

(Contd. of page 2)



# Safety Data Sheet acc. to OSHA HCS

Printing date 09/12/2014 Version 6 Reviewed on 09/12/2014

Product name: Einpressfluid OH 723

Further information about storage conditions:

Protect from heat, direct sunlight and UV-rays.

Protect from heat, direct sunlight and UV-rays. Store in cool, dry conditions in well sealed receptacles.

Storage stability under the described conditions: 24 months.

Specific end use(s)
 No further relevant information available.

### 8 Exposure controls/personal protection

· Additional information about design

of technical systems: No further data; see item 7.

Components with limit values that

require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that

have to be monitored at the workplace.

Additional information: The lists that were valid during the creation were used as basis.

Personal protective equipment:

General protective and hygienic

measures:

The usual precautionary measures for handling chemicals should be followed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Breathing equipment: Use suitable respiratory protective device in case of insufficient ventilation.

Not necessary if room is well-ventilated. Protective gloves or protective skin cream

Material of gloves Nitrile rubber, NBR

Penetration time of glove material At a glove thickness of about 0,4 mm the value of the permeation breakthrough in

accordance with EN 374 is for chemically similar products according to the manufacturer:

>480 min. (Degradation EN 374 rating class 6)

These statements are based on laboratory test methods which could not simulate working conditions exactly. The responsibility rests with the end user for choosing the right gloves

for his application.

Eye protection: Goggles recommended during refilling.

· Body protection: Protective work clothing

### 9 Physical and chemical properties

· General Information

· Protection of hands:

Appearance:
Form:
Color:
Colorless
Odor:
Odorless
Odour threshold:
PH-value:
Not applicable.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
'Pour point

Flash point:
Flammability (solid, gaseous):
Ignition temperature:

Undetermined.
Undetermined.

< -50 °C (< -58 °F)

> 150 °C (> 302 °F)

Not applicable.

> 200 °C (> 392 °F)

Not determined.

· Danger of explosion: Product is not explosive. However formation of explosive air/vapour mixtures above the

flash point or in case of strong misting is possible.

Explosion limits:

Lower: Not determined. Not determined.

• Vapor pressure: Not determined.

Density at 15 °C (59 °F): 0.80 g/cm³ (6.676 lbs/gal)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Kinematic at 40 °C (104 °F): 5.5 mm<sup>2</sup>/s

(Contd. on page 4)



# Safety Data Sheet acc. to OSHA HCS

Printing date 09/12/2014 Version 6 Reviewed on 09/12/2014

Product name: Einpressfluid OH 723

(Contd. of page 3)

· Solvent content:

VOC (EC) None VOC (California) None

Other information Oxidising properties: not determined

# 10 Stability and reactivity

· Thermal decomposition / conditions

to be avoided: No decomposition if used according to specifications.

· Incompatible materials: Strong oxidizing agents

· Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

#### 68649-11-6 1-Decene, Dimer, Hydrogenated

 Oral
 LD50
 > 5000 mg/kg (rat)

 Dermal
 LD50
 > 3000 mg/kg (rabbit)

 Inhalative
 LC50 / 4h
 1.17 mg/l (rat)

Primary irritant effect:

on the skin: Repeated/long exposure may cause skin dryness and in consequence skin irritations.

· on the eye: No irritating effect.

· Sensitization: No sensitizing effects known.

Additional toxicological information: The product shows the following dangers according to internally approved calculation

methods for preparations:

Harmful

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety &

Health Administration) Harmful by inhalation.

See also Section 15

### 12 Ecological information

· Aquatic toxicity:

68649-11-6 1-Decene, Dimer, Hydrogenated

LL50 / 96h | > 1000 mg/l (Oncorhynchus mykiss)

NOEC / 21d | 125 mg/l (Daphnia magna)

· Acute ecotoxicity:

68649-11-6 1-Decene, Dimer, Hydrogenated

EL50 / 72h | > 1000 mg/l (Scenedesmus)

Persistence and degradability Not easily biodegradable

Bioaccumulative potential No further relevant information available.

· Ecotoxical effects:

Behavior in sewage processing

**plants:** The product can be mechanically separated

### 13 Disposal considerations

· Waste treatment methods

Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach

sewage system.

· European waste catalogue

12 01 07\* mineral-based machining oils free of halogens (except emulsions and solutions)

15 01 10\* packaging containing residues of or contaminated by dangerous substances

For the product: 12 01 07

Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

(Contd. on page 5)



# Safety Data Sheet acc. to OSHA HCS

Printing date 09/12/2014 Version 6 Reviewed on 09/12/2014

Product name: Einpressfluid OH 723

Waste disposal key: 15 01 10

(Contd. of page 4)

4 Transport information	
· UN-Number · DOT, IMDG, IATA · ADR	Void Void.
· UN proper shipping name · DOT, ADR, IMDG, IATA	Void
· Transport hazard class(es)	
· DOT, IMDG, IATA · Class	Void
· ADR · Class · Label	Void Void.
· Packing group · DOT, IMDG, IATA · ADR	Void Void.
Environmental hazards: Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MAR the IBC Code	POL73/78 and Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
· ADR · Excepted quantities (EQ): · Limited quantities (LQ) · Transport category · Tunnel restriction code	Void Void. Void. Void.
· IMDG	Void.
· IATA	Void.

## 15 Regulatory information

- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

See section 8 for information.

AGW (German Maximum Workplace Concentration)

68649-11-6 1-Decene, Dimer, Hydrogenated

5 mg/m³

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 6)

(Contd. of page 5)



## **Safety Data Sheet** acc. to OSHA HCS

Reviewed on 09/12/2014 Printing date 09/12/2014 Version 6

Product name: Einpressfluid OH 723

· OSHA-Ca (Occupational Safety &

**Health Administration)** 

Harmful by inhalation.

68649-11-6 1-Decene, Dimer, Hydrogenated

See also Section 11.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Reasons for alterations General revision.

· Relevant phrases H304 May be fatal if swallowed and enters airways.

H332 Harmful if inhaled.

R20 Harmful by inhalation.

R65 Harmful: may cause lung damage if swallowed.

Department issuing MSDS: Department of Research & Development

· Date of preparation / last revision 09/12/2014 / 5

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the · Abbreviations and acronyms:

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association VOC: Volatile Organic Compounds (USA, EC) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent
NOEC: no observed effect concentrations
CAS: Chemical Abstracts Service (division of the American Chemical Society)

\* \* Data compared to the previous

version altered. USA